



Do you sometimes find your personal car parking space has been taken by another inconsiderate driver who ignores your 'private parking' sign?



The remote Parking Guard could well be your answer!

Introducing the PARKING GUARD

Easy to use, the PARKING GUARD provides an economical way to protect your private parking bay from unauthorised use. PARKING GUARD is supplied complete and ready for installation, including mounting bolts, a remote control unit, and a spare battery (for battery only powered models). The unit is easy to install, and can be fitted by any competent handy-person. For security, all mounting bolts are located under a security cover which needs to be removed using the key provided with the unit.



Unlike mechanical gates and manual bollards, that require the user to get out of their car, the PARKING GUARD is operated by remote control from the comfort and safety of your vehicle. Multiple remote controls can be programmed onto the same PARKING GUARD unit, and multiple PARKING GUARD units can be integrated together for use in commercial premises and apartment blocks.

Product Features:

- Solid steel construction.
- Water and dust tight for outdoor use.
- Automatic detection of overload and load reversal (with contact alarm).
- Strong and vandalism resistant.
- Manual emergency over-ride.
- Zinc plated and powdercoated for superior corrosion protection.

Model	PG-B1	PG-B2	PG-B3
Description	Solar Powered Parking Guard with integrated battery.	Rechargeable Battery only.	240V AC Powered Parking Guard with battery backup.
Supply Voltage	Solar / 6V Internal battery	6V Internal battery	240V AC (Mains Power)
Max. Power	36W	36W	36W
Items Included	Solar parking guard, mounting bolts, rechargeable battery, back-up battery charger, one remote control.	Parking guard, mounting bolts, 2 rechargeable batteries, one remote control, battery charger.	Parking guard with internal backup battery, mounting bolts, one remote control.
Rise / Fall Delay Time	3-4 seconds	3-4 seconds	3-4 seconds
Radio Transmit Range	0-20 Metres	0-20 Metres	0-20 Metres
Working Temperature	-30° to +60° C.	-30° to +60° C.	-30° to +60° C.
Dimensions	460 x 500 x 70mm	460 x 500 x 70mm	460 x 500 x 70mm
Shipping Weight	16 kg	17 kg	17 kg

CONTACT:

Phone: (08) 9246 9923
Fax: (08) 9246 9963
Email: ask-us@accesstechnologies.com.au
Web: www.accesstechnologies.com.au

